



Automatic Rising Bollards

Generated on 14.07.2017

Detailed description

Automatic Rising Bollard 'iBollard':

Hydraulic rising/ active bollards are suitable for high security applications and preventing unauthorised access. The bollard includes a control cabinet, which is recommended to be installed within 10 m of the Bollard system.

Product guidance - As Standard

Operational height:

600 mm.

Width (diameter):

215 mm.

Material/ Finish:

Stainless steel finish.

Electrical:

- HPU (Hydraulic Power Unit).
- 100 mm diameter red/ green LED traffic light head with monitored safety circuit.

Product specification

Manufacturer

- Name: Frontier Pitts Ltd
- Web: www.frontierpitts.com
- Email: sales@frontierpitts.com
- Tel: +44 (0)1293 548301
- Fax: +44 (0)1293 560650
- Address: Crompton House, Crompton Way, Manor Royal Industrial Estate, Crawley, West Sussex RH10 9QZ



Frontier Pitts Ltd
Crompton House
Crompton Way
Manor Royal Industrial Estate
Crawley
West Sussex
RH10 9QZ

Tel: +44 (0)1293 548301

www.frontierpitts.com
sales@frontierpitts.com

Product reference Automatic Rising Bollard

Actuation/ Safety Not required
100 mm diameter red/ green LED traffic light head with monitored safety circuit - Highly recommended to be installed with all Bollard systems.



200 mm diameter red/ green LED traffic light head with monitored safety circuit - Highly recommended to be installed with all Bollard systems.

Audible alarms

Induction loop/ Vehicle detector loop system

Light curtain

Photocell

Signage

Ultra sonic sensors