PLATINUM HINGED GATE

- DOUBLE LEAF





The LPS1175 Platinum Hinged Gate has withstood forcible attack to LPS1175 Security Rating SRI (AI), SR2 (B3) & SR3 (C5). Available in a double leaf width up to 10m.

- Standard height: 2400mm. Max Height 4000mm
- Fully Welded Construction
- LPS1175 SR1 (A1), SR2 (B3) & SR3 (C5) rated infill
- Bespoke Manufacturing
- Certification number 1059b/07 and 1059b/09



Benefits & Features

- Successfully Forcible Attack Tested by BRE to SRI, SR2 & SR3 resisting an intensive attack test program in accordance with LPS I 175: Issue 7.3.
- Security Rating I
- series of attacks lasting I minutes
- Security Rating 2
- series of attacks lasting 3 minutes
- Security Rating 3
- series of attacks lasting 5 minutes
- · The Hinged Gate is a swing security gate, which is ideal for sites where there is a limited area for the runback of a sliding gate
- · Hinged Gate leaves can be automated with our range of Trojan or Dutyman Actuators

Trojan Actuator

- Designed to automate larger, heavier gates
- 100% duty rating
- designed for continuous operation
- Underground and surface mounted models available

Dutyman MkII Actuator

- · A surface mounted, self-contained electro-mechanical drive mechanism
- The actuator will operate double-leaf gates up to 10m and heights up to 4m
- 100% duty rating
- designed for continuous operation

Options

- 100/200mm Traffic Light System
- High Security Cabinet
- Can be interfaced to any access control systems
- Vehicle detector loops
- · Safety photocell beams
- Flashing beacons
- Audible alarm
- Safety Edge

Civil Requirements

Double Leaf with small Dutyman Drive (millimetres) Gate post foundation L: 1000 x W: 1100 x D: 900 Ground stop L: 600 x W: 600 x D: 300

Note: Power and control wiring ducts to be incorporated into foundations

Electrical Requirements

- Dependent on Automation
- * Depending on configuration
- ** This is subject to a risk assessment to ensure the automatic equipment complies to BS EN 12453



